		ODES	1	1					ORDER DETAILS					STANDARD OPTIONS		
WIDTH "H" "W" HEIGHT	05W 10W	15W	20W	25W	30W	35W	40W		ITEM#	HEIGHT	WIDTH	DEPTH	QTY.		(CHECK IF A	PPLICABLE)
Number Number 05H 14 7/8" 10H 26 7/8"	SIZE CODE NOT	14 1/8" 26 1/8" 37 1/2" 49 1/2" 60 7/8" 72 7/8" 84 1/4" 96 1/4" <u>SIZE CODE NOTE</u> : TO DETERMINE SIZE CODE OF DESIRED HOUSING, 55 SIZED UNITS REPRESENT A 12" NOMINAL SIZE FILTER AND 10 SIZED UI REPRESENT A 24" NOMINAL SIZED FILTER.							1				REQ'D		TER SIZE E REQUIRED	STATIC PRESSURE PORTS (REF. CSD-020)
15H 39" 20H 51"	IE: A 10HX15W UI (1) 24"X24"X11	NIT WOUL	D ACCOM	MODATE					2					2" (N		PORTS ONLY (PLUGGED) WITH GAGES
20H 51 25H 63 1/8"	(1) 24"X12"X11	INAL FILT		D SIDE BY	SIDE.			3					4" (N	DM.)		
30H 75 1/8" 35H 87 1/4"		Ή						4					MATER		SHIP LOOSE	
40H 99-1/4"	99-1/4" FINAL FILTER* ONLY 22"														'ANIZED STEEL 11NIZED STEEL	FINAL FILTER GAGE
FINAL FILTER* W/ 2" OR 4" PREFILTER 22"									5						L STAINLESS	
									EX.	20H	15W	22	10		L STAINLESS	
-==\$)" ——				-	4	— "W" ——	-					WEATHER PROOF GAGE BOX			
FI		-	1		Ē			Γ								
														1 DO		INSULATION TYPE
"H"												1 5/16"			IGHT HAND (STANDARD)	2" THICK, FOIL BACKED, DOUBLE WALL
												VERTICAL	_			WEATHER COVER
										1				RANSITIO] UPSTREA		STANDARD, INTERMITTENTLY WELDED AND CAULKED
															LIFTING LUGS	
														COLLAR: H/WX	2	
ACCESS VIEW 1 3/8" HORIZONTAL															OLLAR: ID	4
STANDARD SPECS:													I	EST PORT	(3/8" NPT)	FLANGES
1. UNIT SHA CAULKE	ALL BE MANUF D WITH AN RTY	/ SEALA								NLY WELDED AND THEN ALL SEAMS ARE ALLED AROUND THE DOOR TO ENSURE A				UPSTREAM OF PREFILTER		PLAIN (STANDARD) C DRILLED (REF. CSD-016)
	POSITIVE FILTER SEAL. 2. ALL UNITS ARE DESIGNED FOR 24"X24" OR 24"X12" NOMINAL SIZED FINAL FILTERS WITH A ONE IN														CASKET	
	AND 24"X24"X2" OR 24"X12"X2" OR 24"X24"X4" OR 24"X12"X4" NOMINAL SIZE PREFIL 3. ALL FILTERS TO HAVE A UPSTREAM SEAL.														OAGRET	DOWNSTREAM
4. LOCKING MECHANISM WILL ONLY BE OPERATED FROM ONE SIDE ON 2 DOOR MODELS. STANDARD GAGE OPTIONS:																
UNLESS O	THER GAGES	ARE SPI		•			,.									
THE OVER		HALL BE	A MAG	NEHELIC	2005 O	R PHO	TOHELIC			LIC 2004 OR PHOTOHELIC A3004, AND UNLESS OTHERWISE NOTED,					LE	VERLOCK
* FINAL FILTEI **ON ONE DO	RS WITH A SIN OR MODELS SI	GLE HE	ADER D	ESIGN.				LSS	PECIFY						P&G MAN	
SIDE FOR LO	ORM	IATIC	N				IF YOU DO NOT SEE THE OPTIONS YOU REQU THE MANUFACTURER CAN CUSTOM DESIGN Y HOUSING TO NEARLY ANY SIZE AND SPECIFIC					PHONE NO.: 252-946-9110 DR CM				
										A PKB ADDED 4" PREFILTER OPTION 8/1/2012				DAS 8/2/2012		
										REV. DRAWN BY DATE DESCRIPTION: APPR. BY DATE				SALE	S DRAWING	
										THE DEVICE DEPICTED AND DESCRIBED HEREON EMBODIES PROPRIETARY INFORMATION OWNED BY P&G MANUFACTURING INFORMATION OWNED BY P&G MANUFACTURING INFORMATION OWNED BY P&G MANUFACTURING				N INCHES	DRAWN BY: DATE: WMA 5/10/10	DWG SCALE: NTS
NC TEP RG RES											INC. ALL DESIGN, MANUFACTURING, FOLLERANCES FF REPRODUCTON, SALES, AND PATENT RIGHT REGARDING THIS DEVICE OR DRAINING ARE ARE: DI RESERVED IX OF WHERE EXPLICIT RIGHT IS GRANTED IN WRITING. AN			<u>±1/8"</u> <u>±.125"</u> <u>±1°</u>	APPROVED BY: DATE: DRAV	VING NO.: SHEET OF REV. 0 D-005 1 1 A